

# Dynamos XL

## Automation for sliding gates up to 2500 kg

### QUICK AND ROBUST

Dynamos XL in 24 Vdc and 230 Vac versions: maximum power applied to the mechanical reliability of the Dynamos family.

The base in cast aluminium, the plastic parts in ABS with UVA protection and the polyester coatings make this product resistant to atmospheric agents.

### INTENSIVE USE

Dynamos XL is designed for installation in industrial and commercial settings, or anywhere that requires maximum reliability with intensive use.

Set up for inductive end-of-travel stop.



1.



2.



3.

### 1. BUILT-IN CONTROL UNIT

*The new StarG8 control unit, with built in receiver, guarantees the highest performance*

### 2. EASY AND STRONG RELEASE

*Release lever with customised key*

### 3. STURDY FRAME

*The high thickness of the die-cast aluminium frame are ideal for an intensive use*

READY FOR



### KINGSPECIALIST APP FOR INSTALLERS

*The KINGspecialist App allows you to complete all installation setup phases directly from your smart phone or tablet.*



**DYNAMOS XL - TECHNICAL DATA**

Code		DYNAMOS XL 1800	DYNAMOS XL 2500
Mains power supply	(Vac 50/60 Hz)	230	
Motor supply	(Vac/Vdc)	24	230
Speed	(m/sec)	0.28	0.17
Weight	(kg)	18	23.5
Cycle of work	(cycles/hour)	60	42
Absorption	(A)	2	3.8
Power	(N)	1120	1390
Protection level	(IP)	44	
Dimensions	(mm)	400x255x390	
Working temperature	(°C)	-20 ÷ +50	

Also available in 110 V version

# Dynamos XL

## MOTORS - AVAILABLE VERSIONS

Code	Motor	Control unit	Radio receiver	Fixing kit	Gate max weight
Dynamos XL 2500	230 Vac	STARG8 AC	•	•	2500 kg
Dynamos XL 1800	24 Vdc	STARG8 24	•	•	1800 kg

Also available in 110 V version

